Assembly and Fitting Instructions for Ceiling Pendant Lights


Note: If in doubt, or difficulty is experienced, consult a qualified electrician.

Before commencing any installation check that the supply circuit is connected to a 5 Amp fuse Outlet.


- 1. Important: Ensure electricity is switched off at the mains before installing or maintaining these fittings.
- 2. The weight of the fitting must be supported by the suspension chain and not by the flexible cable.

Ensure that the bracket (supplied) is fixed to a wooden joist in the ceiling using screws (supplied) or use a suitable fixing to the ceiling, which will support the weight of the fitting. Please check for any wiring or pipes before commencing.

- 3. Feed the flexible cable through the links of chain and into the ceiling cup. Ensure that strain is not placed on the cable.
- 4. Hang chandelier from ceiling bracket.
- 5. Fittings must be earthed. Ensure that all tags or terminals marked connected to the supply Earth (normally a green and yellow wire).
- 6. Connect cables or terminals in the light fittings as shown.



Check that all wires are tight in the terminal block and that no loose strands are left out of the terminal block. Cover the terminal block with insulating tape. This block is not part of the lamp and is supplied to assist assembly.



NB There may also be a loop in/loop out connection in which case a forth connector should be used (not supplied).

- 7. Push up Ceiling Cup and secure in place.
- 8. Ensure arms are spaced with an equal gap between each lampholder.
- 9. Insert lamp(s). See Lampholder for maximum wattage.

WARNING- THIS LUMINAIRE MUST BE EARTHED

We recommend that this light is installed by a qualified electrician in accordance with both current IEE wiring regulations and also current Building Regulations