

P330

Smart 4K PoE Security Camera with 100ft Night Vision

- Person/Vehicle/Animal Detection
- 4K Ultra HD View
- Power over Ethernet
- Two-way Audio



Specifications

Video & Audio	
Image Sensor	1/2.7" CMOS sensor
Resolution	3840*2160(8Megapixels) @25FPS
Lens	f=2.8mm fixed; F=1.6, with IR-cut filter
Video Compression	H.265
Field of View	Horizontal: 105° Vertical: 56° Diagonal: 125°
Day & Night	IR-cut filter with auto-switching
Infrared Night Vision	Up to 30 meters (100ft) (LED: 2pcs/1.8W/850nm)
Color Night Vision	1PCS/4.3W/6500K/700Lumens
Audio	Two way Audio
Frame Rate	2-25FPS

Code Rate	Mainstream: 2048Kbps - 8192Kbps (default:6144Kbps) Sub Stream: 64Kbps - 512Kbps(default: 256Kbps)
Power Requirements	
PoE	IEEE 802.3af, 48V Active
DC Power	DC 12.0V= 1A, <12W
Interface	
Power Port	DC power port
Ethernet Port	One 10M/100Mbps RJ45
SD Card Slot	microSD card slot (Max. 512GB)
Reset Button	YES
Audio	Built-in Microphone&Speaker
Software Features	
Browsers Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Smart Alarm	Motion detection/Person Detection/Vehicle Detection/Animal Detection
Recording Modes	Motion-triggered recording (default); Scheduled recording; 24/7 recording
Smart Home Compatibility	Google Assistant
Working Environment	
Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
Humidity	Operating humidity: 10% ~ 90%
Weatherproof	IP67
Mechanical	
Dimensions	68*63*188mm
Weight	452.4g

Warranty

Limited Warranty

2-year limited warranty. For support, visit <https://support.reolink.com/hc/en-us/>

Gallery & Specs





- ① Power Port
- ② Reset Button
- ③ Network Port
- ④ Port Cover

www.reolink.com