



Residential Wall Mount

FTXF-D / RXF-D sensira

R-32 BLUEEVOLUTION

The residential wall mount unit provides perfect comfort without compromising energy efficiency

The flat front panel blends in easily with any interior décor and is easy to clean. Air is distributed efficiently and evenly, thanks to auto-swing louvres, which direct the discharge air downwards or upwards. The turbo mode means that the room can heat up or cool down rapidly.

Seasonal efficiency values up to A++

The heat exchanger and fan generate one of the highest energy efficiencies across the range (20-60).

Residential Controller App (optional)

The Residential Controller App controls your indoor unit from any location via connection to the cloud. Main functions like temperature set point, operation mode, fan speed, etc can also be controlled via Amazon Alexa or Google Assistant.

Quiet operation down to 20 dB(A)

The different fan settings mean the residential wall mounted unit can be used in offices, hallways, living and bed rooms. With a sound pressure of 20 d(BA), the unit is whisper quiet.

Reliable performance

The extensively tested swing compressor uses inverter technology and small capacity steps to adjust a unit's power and energy demands, delivering energy savings and vibration-free operation.



FTXF20-35D



RXF20-35D



ARC470A1

Indoor Units			FTXF25D	FTXF35D
Capacity	UK Total Cooling	kW	2.44	3.22
	UK Sensible Cooling	kW	1.94	2.35
	Nominal Cooling	kW	2.50	3.30
	Nominal Heating	kW	2.80	3.50
Seasonal Efficiency (EN14825) COOLING	Energy Label		A++	A++
	Pdesign	kW	2.50	3.50
	SEER		6.50	6.50
	Annual Energy Consumption kWh		141	197
Seasonal Efficiency (EN14825) HEATING	Energy Label		A+	A+
	Pdesign	kW	2.40	2.60
	SCOP		4.11	4.11
	Annual Energy Consumption kWh		817	885
Air Flow Rate (Cooling)	High / Nominal / Low / Silent	m ³ /sec	0.142 / 0.100 / 0.076 / 0.06	0.197 / 0.133 / 0.107 / 0.073
Dimensions	Height	mm	286	286
	Width	mm	770	770
	Depth	mm	225	225
Weight		kg	7.50	8.50
Sound Pressure (Cooling)	High / Low / Silent	dBA	40/26/20	43/27/20
Sound Pressure (Heating)	High / Low / Silent	dBA	40/28/21	40/29/21
Sound Power (Cooling)		dBA	54	54

Outdoor Units			RXF25D	RXF35D
Dimensions	Height x Width x Depth	mm	550 x 658 x 275	550 x 658 x 275
Weight		kg	25.50	26
Electrical Details	Power Supply		1ph	1ph
	Running Current	A	Please refer to data book	
	Max Fuse Size	A	16	16
Interconnection Wiring	Core / Cable size		3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)
Pipework	Maximum Length	m	20	20
	Maximum Vertical Rise	m	12	12
	Precharged to	m	10	10
	Additional Charge	g/m	20	20
	Holding Charge	kg	0.45	0.55
Sound Pressure (Cooling)	20-42 High / 50-71 Nominal	dBA	46	48
Sound Pressure (Heating)	20-42 High / 50-71 Nominal	dBA	47	48
Sound Power (Cooling)		dBA	60	61
Operating Range (Cooling) Min / Max	°CDB		-10/48	-10/48
Operating Range (Heating) Min / Max	°CWB		-15/18	-15/18
Air Flow Rate (Cooling)	20-42 High / 50-71 Nominal	m ³ /sec	0.483	0.483

Notes

- > All fan coils are supplied with infrared remote controller ARC470A1
- > Whisper quiet in operation down to 20 dBA
- > The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- > Space saving contemporary wall mounted design

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



FSC

Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com